



Platine 4.250.29



Profiled sheet for single and double skin cladding


Haironville (FR)



- Shorter lengths up to 200 mm are available on request.
- Minimum length 1,800 mm / Maximum length 6,500 mm
- Minimum thickness for horizontal installation: 0.75 mm
- Recommended maximum length for horizontal installation 1,500 mm

Surface mass

Thickness (mm)	0.75
Mass (kg/m ²)	6.84



Overlap

Table of maximum permissible loads in kN/m² as a function of the working spans

For horizontal single skin installation, the span is limited to 3 m.

		2 SUPPORTS		Span (m)	3 SUPPORTS	
		Thickness (mm)			Thickness (mm)	
		0.75			0.75	
Single & double skin	Pressure	1.60		≤ 1.50	1.60	Pressure
	Underpressure	1.60			1.60	Underpressure
	Pressure	1.30		1.60	1.60	Pressure
	Underpressure	1.30			1.60	Underpressure
	Pressure	1.08		1.70	1.41	Pressure
	Underpressure	1.08			1.60	Underpressure
	Pressure	0.91		1.80	1.26	Pressure
	Underpressure	0.91			1.60	Underpressure
	Pressure	0.77		1.90	1.13	Pressure
	Underpressure	0.77			1.60	Underpressure
	Pressure	0.67		2.00	1.01	Pressure
	Underpressure	0.67			1.34	Underpressure